



DX0-1525 Cartridge

The modern, eco-friendly solution to fluid conditioning.

- Particle filtration down to **0.1 μ**
- Designed for mineral and synthetic fluids
- Hydraulic, lube and gear applications
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
- Minimised fluid oxidation
- Mitigation and reduction of **varnish**
- Increased production uptime
- Reduced fluid changes
- Eco-friendly
- Easy to service
- Small footprint
- **100% Recycled** media



Maintaining healthy fluid by removing:

- **Bacteria**
- **Water (free and emulsified)**
- **Oxidation products (Sludge and resin)**

Technical Specifications

| | |
|--------------------------------|--------------------------|
| Part No. | DX0-1525 |
| Weight (Dry) | 1.15 kg |
| Weight (Saturated) | Up to 1.4ltrs |
| Flow capacity | 0.5 lpm @32 cSt |
| Water absorption, free & bound | Up 0.85Ltrs |
| Min and max limits | Min 0°C - Max 100°C |
| Material | PP Cellulose mix |
| Package dimensions | 152 mm x 152 mm x 230 mm |




© 2021 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



Authorised Distributor



t: +44 1264 860186
e: spares@simplexturbulo.com

STC is a member of  **SIMPLEX**
ENGINEERING GROUP



Delta-Xero Distribution Ltd
Unit 5, Pennant Park, Standard Way,
Fareham, Hampshire,
PO16 8XU
t: +44 2392 874 755
e: sales@delta-xero.com