



## DXO Powertrain Cartridge

The modern, eco-friendly solution to fluid conditioning.

- Particle filtration down to **0.1 µm**
- Designed for mineral and synthetic fluids
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
- Extend oil drain intervals
- Minimised fluid oxidation
- Mitigation and reduction of varnish
- Increased production uptime
- Reduced fluid changes
- Eco-friendly
- Easy to service
- **100% Recycled** media



Maintaining healthy fluid by removing:

- Abrasive material to down 0.1 µm
- Bacteria
- Water bound free and emulsified
- Oxidation products (Sludge and resin)
- Siloxane

### Technical Specifications

Part No.	DXPT
Weight ( Dry )	1.7 kg
Weight ( Saturated )	Up to 4.0 kg (Fluid dependent)
Flow capacity	Up to 7 L/min (Viscosity dependent)
Water absorption, free & bound	Up to 2600 ml
Min and max limits	Min 0°C. Max 100°C
Material	PP Cellulose mix
Package dimensions	192 mm x 192 mm x 265 mm



© 2021 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



Authorised Distributor



t: +44 1264 860186

e: spares@simplexturbulo.com

STC is a member of

